Macroscopic, Hand-held Magnetic Monopole Device

Carlos Omeñaca Prado

December 2025

DECLARACIÓN DE DOMINIO PÚBLICO Y RENUNCIA DE DERECHOS

(CC0 1.0 Universal — Public Domain Dedication)

Yo, **Carlos Omeñaca Prado**, declaro que esta obra,
incluido su contenido técnico, dibujos, datos y anexos,
se entrega al **DOMINIO PÚBLICO GLOBAL**. Renuncio íntegramente
a cualquier derecho de autor o patente, y autorizo su uso,
reproducción y modificación sin restricción alguna.

Fecha: 3 de diciembre de 2025
Firma: Carlos Omeñaca Prado

PUBLIC DOMAIN AND RIGHTS WAIVER DECLARATION

(CC0 1.0 Universal — Public Domain Dedication)

I, **Carlos Omeñaca Prado**, hereby declare that this work,
including all its technical content, drawings, data and appendices,
is hereby released into the **GLOBAL PUBLIC DOMAIN**.
I completely and irrevocably waive any copyright or patent rights,
and authorize its use, reproduction and modification
without any restriction or limitation.

Date: December 3, 2025
Signature: Carlos Omeñaca Prado

MACROSCOPIC, HAND-HELD MAGNETIC MONOPOLE DEVICE

Carlos Omeñaca Prado

Año: 2025

Abstract

This work presents a fully engineered architecture for a macroscopic, hand-held magnetic monopole device constructed within the theoretical framework of Quark-base Cosmology, where the magnetic field is interpreted as the vorticity of the etheric plasma (Ψ-field). In this reinterpretation of electrodynamics, Maxwell's equation

$$\nabla \cdot \mathbf{B} = 0$$

remains strictly valid globally, since B is a rotational field with no fundamental magnetic charges.
However, topological defects of the Ψ phase—specifically, phase vortices with displaced cores and confined return strings—allow the emergence of effective magnetic charges, measurable as monopole-like sources over macroscopic regions.//

The objective of this work is to demonstrate that, by stacking and phase-aligning multiple microscale Ψ-vortex modules hosted in twisted bilayer graphene (TBG) and channeling their collective flux through a ferromagnetic macroscopic structure, one obtains a unidirectional outflow of magnetic flux from one face of a tangible 3-cm solid body, with the return path completely confined inside the volume, thus producing an externally observable monopolar magnetic field.//

The final device is a hand-held element ($\approx$ 35 mm $\times$ 18 mm) that behaves, for all practical measurement purposes, as a magnetic monopole.

Contents

1 Physical Mechanism Enabling Monopole Emergence **6**
- 1.1 Etheric Interpretation of **B** and the Role of Ψ . . . 6
- 1.2 Vortex-Based Magnetic Current in TBG . . . 6
- 1.3 From Microscale Monopoles to a Macroscopic Monopole . . . 7

2 General Engineering Architecture **7**

3 Device Design Overview **8**

4 TBG Ψ-Module Engineering and Internal Vortex Geometry **10**
- 4.1 Functional Objective of a Single Ψ-Module . . . 10
- 4.2 Physical Layout of the TBG Chip (Drawable Geometry) . . . 10

5 Engineering the Phase-Stiffness Tensor $K_{ij}(x, y)$ **11**
- 5.1 Twist-Angle Gradient . . . 11
- 5.2 Resulting Phase-Stiffness Field . . . 12

6 Vortex Core Positioning **12**
- 6.1 Nucleation . . . 12
- 6.2 Deterministic Core Pinning . . . 12

7 Return-String Routing and Confinement **13**
- 7.1 Pump-Induced $|\Psi|^2$ Landscape . . . 13
- 7.2 Routing the String . . . 13

8 Micro-Ferromagnetic Extraction Yoke **13**
- 8.1 Structure . . . 13
- 8.2 Function . . . 14

9 Full Parameter Table (Unambiguous for CAD Drawings) **14**

10 Module Array Architecture and Macroscopic Flux Summation **15**
- 10.1 Overview of the Multiscale Assembly . . . 15
- 10.2 Physical Arrangement of Modules Inside a 3D Block . . . 15
  - 10.2.1 Module block dimensions . . . 15
  - 10.2.2 Grid layout . . . 16
- 10.3 Module Orientation Relative to Macroscopic Device Axes . . . 16
- 10.4 Mesoscopic Ferromagnetic Collector Structure . . . 16
  - 10.4.1 Geometry . . . 16
  - 10.4.2 Central emission conduit . . . 17
- 10.5 Internal Return-Flux Manifold (Hidden Pole) . . . 17
  - 10.5.1 Back manifold design . . . 17
  - 10.5.2 Routing of module-level return strings . . . 17
  - 10.5.3 Purpose . . . 17
- 10.6 Summation of Magnetic Flux . . . 18
  - 10.6.1 Flux per module . . . 18
  - 10.6.2 Macroscopic flux . . . 18

10.6.3 Field at the device surface . . . 18
10.7 Phase-Coherence Requirements Across the Array . . . 19
10.8 Mechanical Integration and Thermal Conditions . . . 20
10.8.1 Housing . . . 20
10.8.2 Cooling . . . 20
10.8.3 Vibration tolerance . . . 20
10.9 Result: Emergence of a Single Macroscopic Monopole . . . 20

11 Flux Collector, Emission Face, Return-Manifold Geometry, and External Field Characteristics 21
11.1 Role of the Flux-Collector Assembly . . . 21
11.2 Collector Plate Geometry . . . 21
11.2.1 Physical Dimensions . . . 21
11.2.2 Perforation Grid . . . 21
11.2.3 Function . . . 21
11.3 Central Flux-Concentration Conduit ("Monopole Chimney") . . . 22
11.3.1 Geometry . . . 22
11.3.2 Purpose . . . 22
11.4 Emission Face Engineering . . . 22
11.4.1 Front-Face Geometry . . . 22
11.4.2 Field Equalization Layer . . . 22
11.4.3 Monopolar Output . . . 23
11.5 Internal Return-Manifold Architecture . . . 23
11.5.1 Placement . . . 23
11.5.2 Functional Requirements . . . 23
11.5.3 Structural Details . . . 23
11.5.4 Purpose in Quarkbase Interpretation . . . 24
11.6 External Magnetic Field Characteristics . . . 24
11.6.1 Field Morphology . . . 24
11.6.2 Key Properties . . . 24
11.6.3 Measurement Signatures . . . 24
11.7 Engineering Summary for CAD/Blueprint Drafting . . . 25

12 Longitudinal-Mode Excitation System, Coherence Control, Thermal Management, and Operational Regimes 25
12.1 Purpose of the Longitudinal-Mode Excitation System . . . 25

13 Excitation Frequency, Coupling Mechanism, and Waveguide Architecture 25
13.1 Resonance Frequency Selection . . . 25
13.2 Pump Delivery Waveguide . . . 26
13.2.1 Waveguide Geometry . . . 26

14 Coherence Control in the Ψ-Module Network 26
14.1 Mechanism of Coherence Enhancement . . . 26
14.2 Array-Level Phase Alignment . . . 27

15 Thermal Management and Cryogenic Support **27**
15.1 Cooling Architecture . . . 27
15.2 Thermal Gradients . . . 27

16 Operational Regimes: Three Modes of Use **28**
16.1 Mode A — High-Coherence Monopole Output . . . 28
16.2 Mode B — Low-Coherence Monopole Output (Pump OFF) . . . 28
16.3 Mode C — Warm Operation (10–80 K) . . . 28

17 Stability Considerations Under Operational Shifts **29**
17.1 Thermal Cycling . . . 29
17.2 Pump-Power Instability . . . 29
17.3 Environmental Magnetic Noise . . . 29

18 Device Assembly, Mechanical Integration, Full 3D CAD Specification, Materials, Shielding, and Safety Constraints **29**
18.1 Global Mechanical Architecture . . . 29

19 Active Core: Physical Mount and Alignment **30**
19.1 Core Block Substrate . . . 30
19.2 Module Alignment Grid . . . 30
19.3 Interlayer Spacing . . . 31

20 Flux Collector and Central Emission Conduit (3D CAD) **31**
20.1 Collector Plate (Top View Specification) . . . 31
20.2 Central Conduit (“Chimney”) . . . 31
20.3 Mechanical Joining . . . 31

21 Return-Flux Manifold (Back-Half Assembly) **32**
21.1 Manifold Geometry . . . 32
21.2 Micro-Yoke Interface . . . 32
21.3 Manifold Sealing . . . 32

22 Cryogenic Sleeve Assembly (Thermal System) **32**
22.1 Cryogenic Chamber . . . 32
22.2 Cooler Attachment . . . 33
22.3 Temperature Sensors . . . 33

23 THz Waveguide and Diffusion System **33**
23.1 Waveguide Specification . . . 33
23.2 Diffuser Layer . . . 33

24 Outer Structural Shell and Shields **34**
24.1 Outer Shell . . . 34
24.2 Magnetic Shielding Layers . . . 34

25 Fastening and Assembly Strategy **34**
25.1 Subassembly Order . . . 34
25.2 Tolerances . . . 35

26 Operational Safety Constraints **35**
26.1 Magnetic Field Exposure . . . 35
26.2 Cryogenic Hazards . . . 35
26.3 THz Radiation Safety . . . 35
26.4 Mechanical Shock Tolerance . . . 35

27 CAD Summary: Exact Drawables **36**

28 System Integration, Calibration Protocols, External Performance Characterization, and Failure Modes **36**

29 System Integration **36**
29.1 Mechanical Integration . . . 36
29.1.1 Module-to-Collector Alignment . . . 36
29.1.2 Chimney–Collector Bond . . . 37
29.1.3 Manifold Coupling . . . 37
29.2 Cryogenic Integration . . . 37
29.2.1 Cold Finger Mounting . . . 37
29.2.2 Thermal Expansion Compensation . . . 37
29.3 Electromagnetic Integration . . . 38
29.3.1 THz System Calibration . . . 38
29.3.2 Shielding Verification . . . 38

30 Calibration Protocols **38**
30.1 Cryogenic Calibration . . . 38
30.2 Monopole-Flux Calibration . . . 38
30.3 Coherence Calibration . . . 39

31 External Performance Characterization **39**
31.1 Spatial B-Field Profile . . . 39
31.2 Temporal Stability . . . 39
31.3 Dynamic Response . . . 39

32 Failure Modes and Mitigation **40**
32.1 Vortex Drift or De-Pinning . . . 40
32.2 Flux Leakage (Back or Sides) . . . 40
32.3 THz Waveguide Misalignment . . . 40
32.4 Cryogenic Failure . . . 40

33 Conclusion **41**
33.1 Scientific Impact . . . 41
33.2 Final Statement . . . 41

34 References **42**

1 Physical Mechanism Enabling Monopole Emergence

1.1 Etheric Interpretation of B and the Role of Ψ

In Quarkbase Cosmology, the electromagnetic field originates from the dynamical properties of the underlying etheric medium Ψ. The **magnetic field** is defined as:

$$\mathbf{B} = \nabla \times A_\Psi, \tag{1}$$

where A_Ψ is an effective gauge-like potential encoding the transverse vorticity of the etheric plasma.

A consequence is that **Ψ-phase singularities** (vortices) act as centers where vorticity is concentrated and can be coherently manipulated. When a Ψ-vortex is strongly anisotropic—its core displaced, and its return string geometrically guided—then the magnetic flux loops close along a hidden internal path, while externally **all field lines appear to diverge from a single point**.

This produces a **quasi-Dirac monopole** consistent with

$$\nabla \cdot \mathbf{B} = 0, \tag{2}$$

because the hidden return string acts as the counterpart of the missing pole.

1.2 Vortex-Based Magnetic Current in TBG

Twisted bilayer graphene at angles near the magic angle supports a Ψ-superconducting state characterized by a phase θ and stiffness tensor K_{ij}. The Ψ-supercurrent is:

$$\mathbf{j}_Q = \kappa |\Psi|^2 \left(\nabla\theta - A_\Psi\right), \tag{3}$$

and gives rise to Meissner-like expulsion of effective magnetic field and quantized vortex flux.

Inside each TBG module the engineered configuration includes:

1. **A single Ψ-vortex** nucleated by a weak normal magnetic field.
2. **A controlled spatial anisotropy** in K_{ij} created by:
   - twist-angle gradient,
   - uniaxial strain,
   - localized longitudinal-mode excitation of Ψ.
3. **A displaced vortex core**, stabilized near one edge of the chip.
4. **A confined return string**, guided along the opposite edge.

This intrinsic asymmetry ensures that the external magnetic flux emerging from the chip originates from **one sharply localized region**, while the flux-return is hidden along a thin internal corridor.

Each TBG unit therefore behaves as an elementary **Ψ-monopole module**.

1.3 From Microscale Monopoles to a Macroscopic Monopole

A single TBG vortex produces only micrometric-scale flux patterns. However, the mechanism scales linearly:

$$\Phi_{\text{total}} = \sum_{n=1}^{N} \Phi_{\Psi,n}. \tag{4}$$

By embedding **hundreds to thousands** of Ψ-monopole modules in a confined volume ($\approx 5 \times 5 \times 5$ mm), and by synchronizing their vortex orientation:

- All outward flux contributions **add constructively** at one macroscopic face.
- All return paths **merge into a single internal ferromagnetic channel**, invisible externally.

The macroscopic flux exiting the front face can reach magnitudes comparable to those of a small permanent magnet, yet with a **strict absence of the opposite pole** on the accessible surfaces.

This constitutes the macroscopic **Quarkbase monopole device**.

2 General Engineering Architecture

1. **Geometry of each TBG module**
   - chip dimensions,
   - position of vortex core,
   - path of the return string,
   - micro-ferromagnetic yoke coupling.
2. **Arrangement of the Ψ-modules in a 3D block**
   - grid spacing,
   - alignment,
   - electrical/thermal interfaces.
3. **Macroscopic ferromagnetic structure**
   - geometry of the main collector,
   - monopolar emission face,
   - internal return-flux channel,
   - material parameters (μ_r, saturation flux density).
4. **Longitudinal Ψ excitation system**
   - THz injection ports or waveguides,
   - resonance conditions,

- power thresholds.

5. **Boundary conditions**
    - thermal stabilization (Tc range),
    - stray-field suppression,
    - requirements for topological stability of the vortex ensemble.

3 Device Design Overview

Below is the high-level mechanical description suitable for translation into a 3D engineering model:

- **Overall shape:** solid cylinder
    - length: 35 mm,
    - diameter: 18 mm.
- **Active region:** central cubic chamber
    - $5 \times 5 \times 5$ mm,
    - containing the array of Ψ-modules.
- **Flux-emitting face:**
    - circular, diameter 6–8 mm,
    - sole region where **B**-lines exit the device.

Figure 1: flux-emitting face (6–8 mm)

- **Flux-return pathway:**
  - internal ferromagnetic ring or serpentine channel,
  - embedded in the posterior half of the body,
  - fully shielded by high-μ metal.
- **Longitudinal-mode excitation ports:**
  - THz micro-waveguide entering from lateral side,
  - terminating near the Ψ-module block.
- **Mounting constraints:**
  - total device must withstand handling,
  - field emission region must remain fixed relative to internal modules,
  - no external access to return path.

This global picture ensures that the monopole effect is unambiguous and robust.

4 TBG Ψ-Module Engineering and Internal Vortex Geometry

4.1 Functional Objective of a Single Ψ-Module

Each TBG Ψ-module acts as an **elementary quasi-monopole generator**. Its function is to host one **stable, displaced Ψ-vortex**, whose emergent magnetic flux exits the chip through a well-defined region, whereas the compensating return flux is **internally confined** along a guided string.

A macroscopic monopole is ultimately the sum of hundreds to thousands of these modules, but each module must independently satisfy:

1. **A single vortex core**, pinned deliberately at one corner.
2. **A controlled anisotropy tensor** $K_{ij}(x, y)$ to polarize the phase gradient.
3. **A longitudinal-mode pump field** tuned near the Ψ resonance to enhance coherence.
4. **A ferromagnetic micro-yoke** extracting outward flux while hiding the return.

The Ψ-physics is grounded in GL-type derivations in which

$$j_Q = \kappa |\Psi|^2 \left(\nabla\theta - A_\Psi\right), \tag{5}$$

describes superflow in graphene without Cooper pairs. The enhancement of coherence under THz excitation follows the expected longitudinal-mode response.

4.2 Physical Layout of the TBG Chip (Drawable Geometry)

Each Ψ-module uses a **rectangular TBG flake** of dimensions:

- **Width (x-axis):** 20 μm
- **Height (y-axis):** 20 μm
- **Thickness:** 0.7 nm × 2 layers (graphene bilayer)
- **Substrate:** h-BN (50–80 nm thickness), with low dielectric screening compatible with predicted Quarkbase Tc enhancement.

A **flat rectangular chip** is drawn with:

- Left edge = **high stiffness region**
- Right edge = **low stiffness region**
- Vortex core intentionally displaced toward the **upper-left corner**

Explicit coordinate system:

- Bottom-left: $(0, 0)$
- Top-right: $(20\,\mu\text{m},\ 20\,\mu\text{m})$


Schematic top-down view of a single 20 µm × 20 µm twisted bilayer graphene Ψ-module: left edge = high-stiffness region (darker), right edge = low-stiffness region (lighter). The displaced vortex core (black dot) sits near the upper-left corner, a 0.8 % strain patch overlays the left side, the return trench runs along the lower-right edge, a micro U-shaped ferromagnetic yoke is located at the lower-right corner, and the output pillar appears near the upper-right edge.

Figure 2: Single 20 µm × 20 µm TBG Ψ-module, showing stiffness gradient, vortex displacement, strain patch, return-string trench, micro-yoke, and output pillar

5 Engineering the Phase-Stiffness Tensor $K_{ij}(x, y)$

A displaced vortex requires strong **directional anisotropy**. This is physically supported by mechanisms documented in available Quarkbase-based analyses, including strain–curvature coupling and twist-angle modulation of the etheric channel density.

5.1 Twist-Angle Gradient

Spatial tuning of electron–Ψ coupling and cavity geometry allows the imposition of a **linear twist deviation**:

$$\alpha(x) = \alpha_0 + \Delta\alpha \left(1 - \frac{x}{20\,\mu\text{m}}\right), \tag{6}$$

where:

- $\alpha_0 = 1.10°$,

- $\Delta\alpha = +0.12^\circ$.

This may be drawn as a **gradient arrow** from right $\rightarrow$ left.

5.2 Resulting Phase-Stiffness Field

A GL-type phase functional of the form

$$F_{\text{phase}} = K_{ij}(x,y)\,(\partial_i\theta - A_i)\,(\partial_j\theta - A_j) \tag{7}$$

describes the anisotropic energetics.

Assign:

$$K_{xx}(x) = K_0\left(1 + 0.25\,\frac{20-x}{20}\right), \tag{8}$$

$$K_{yy}(x) = K_0\left(1 + 0.05\,\frac{20-x}{20}\right), \tag{9}$$

$$K_{xy} = K_{yx} = 0. \tag{10}$$

Thus, K_{xx} increases by **25%** from right to left, and K_{yy} by **5%**. This forces the Ψ-phase to minimize gradient energy by aligning $\nabla\theta$ predominantly along $+x$, pushing the vortex core toward the left boundary.

6 Vortex Core Positioning

6.1 Nucleation

A uniform out-of-plane field $B_{\text{ext}} \sim 0.1$–0.5 mT nucleates a single vortex, consistent with Meissner-like suppression of transverse vorticity.

6.2 Deterministic Core Pinning

The vortex settles at the minimum of:

$$E_{\text{core}}(x,y) = \frac{\Phi_0^2}{4\pi\mu_0\Lambda(x)} + U_{\text{strain}}(x,y), \tag{11}$$

where $\Lambda(x) = 1/(\mu_0 K_{xx}(x))$ is the effective Pearl penetration-depth analog, and U_{strain} is specified by engineered strain.

A **biaxial strain patch** is applied:

$$\varepsilon(x,y) = \begin{cases} 0.8\% & \text{if } x < 6\,\mu\text{m},\ y > 14\,\mu\text{m}, \\ 0 & \text{otherwise.} \end{cases} \tag{12}$$

Curvature–absorbance analyses indicate that etheric-channel density (and therefore Ψ properties) scale linearly with strain.

The vortex core becomes pinned near:

$$(x_0, y_0) \approx (4\,\mu\text{m},\ 17\,\mu\text{m}). \tag{13}$$

7 Return-String Routing and Confinement

The topological string (branch cut) associated with the vortex phase singularity is forced to align with regions of **minimum stiffness** and **minimum** $|\Psi|^2$.

7.1 Pump-Induced $|\Psi|^2$ Landscape

Longitudinal-mode analyses predict resonant enhancement of Ψ-coherence at $\omega \approx \omega_\Psi$. A **THz spot** (diameter 8 μm) centered at $(10\,\mu\text{m}, 15\,\mu\text{m})$ produces:

$$|\Psi(x,y)|^2 = |\Psi_0|^2 \left[1 + \eta \, \exp\!\left(-\frac{(x-10)^2 + (y-15)^2}{(4\,\mu\text{m})^2}\right)\right], \tag{14}$$

with $\eta = 0.3$.

The **bottom-right edge** becomes the global minimum of $|\Psi|^2$, defining the preferred corridor for the string.

7.2 Routing the String

The string follows a **pre-patterned trench**:

- depth $\sim$ 30 nm,
- width $\sim$ 80 nm,
- start: $(4\,\mu\text{m}, 17\,\mu\text{m})$,
- path: straight to $(20\,\mu\text{m}, 2\,\mu\text{m})$,
- exit: micro-yoke interface under lower-right corner.

Because $\mathbf{B} = \nabla \times A_\Psi$ in the Quarkbase electrodynamic reinterpretation, the return flux follows this trench and the ferromagnetic interface, remaining internal.

8 Micro-Ferromagnetic Extraction Yoke

8.1 Structure

A soft-magnetic U-shaped yoke is deposited at the lower-right corner:

- Arm thickness: 200 nm,
- Arm width: 2 μm,
- Gap between arms: 100 nm,
- Material: $Ni_{80}Fe_{20}$ (Permalloy), $\mu_r \approx 10^4$.

8.2 Function

- The yoke **absorbs the return flux** emerging from the string at the trench exit.
- The flux is guided into a **vertical pillar** (height 1–2 μm), forming the module's macroscopic flux-output port.
- Since the vortex core is physically remote from the yoke, field lines from the core **flow outward**, not inward; thus the **net flux through the output port is positive**.
- Externally, each module behaves as a **monopole-like north pole**.

9 Full Parameter Table (Unambiguous for CAD Drawings)

Component	Value	Notes
TBG flake size	20×20 μm	Rectangle
Substrate	h-BN, 50–80 nm	Low dielectric screening
Twist gradient	+0.12° across 20 μm	α decreasing left→right
Strain patch	$\varepsilon = 0.8\%$ (top-left)	Vortex pinning anchor
Vortex core	(4 μm, 17 μm)	Stable minimum
THz pump	Center (10,15 μm), diameter 8 μm	Boosts $\|\Psi\|^2$ locally
Trench	30 nm deep, 80 nm wide	Path to (20,2 μm)
Micro-yoke	200 nm thick, $\mu_r \sim 10^4$	Extracts return flux
Output pillar	Diameter 0.5–1 μm	Flux output

Key physical implications:

- The strain-dependent cavity geometry modifies etheric pressure channels, affecting Ψ stiffness and absorption according to established Quarkbase relations.
- The GL-type phase energy produces Meissner-like expulsion and vortex states without Cooper pairs.
- The longitudinal-mode pump raises coherence and sharpens the vortex.
- The string confinement is consistent with **B** being vorticity of the ether, which must form closed loops; the Quarkbase reinterpretation of Maxwell's equations forbids fundamental magnetic charges.
- By forcing the return to flow through an internal trench+yoke, the exterior only sees **one effective pole**.

10 Module Array Architecture and Macroscopic Flux Summation

10.1 Overview of the Multiscale Assembly

The macroscopic monopole device is constructed from:

1. **N elementary Ψ–monopole modules** (TBG vortex chips).
2. **A mesoscopic ferromagnetic collector**, which aggregates the outward flux of all modules.
3. **An internal return-path manifold**, confining all compensating flux inside the device.
4. **A macroscopic emission face**, where the summed flux emerges and is perceived externally as a single magnetic pole.

The array must satisfy:

- Geometric coherence: all module outputs oriented toward the same direction.
- Topological coherence: all return strings routed internally with no leakage.
- Phase coherence: all Ψ-vortices aligned so their net outward flux adds constructively.

10.2 Physical Arrangement of Modules Inside a 3D Block

10.2.1 Module block dimensions

The TBG Ψ-modules are embedded in a **rectangular cuboid** (the "Active Core"):

- **Core dimensions:** $5\,\text{mm} \times 5\,\text{mm} \times 5\,\text{mm}$
- **Module pitch:** $50\,\mu\text{m} \times 50\,\mu\text{m}$ (center-to-center)
- **Total capacity:** up to 10,000 modules (typical operation: 500–2,000)

This pitch allows:

- Clear thermal management
- Mechanical rigidity of the supporting substrate
- Precise routing of micro-yokes and flux channels

10.2.2 Grid layout

- A square array of rows and columns ($\approx 100 \times 100$ positions)
- Each position contains:
  - The TBG chip
  - Its micro-yoke
  - A vertical flux-output pillar
  - A return-flux trench connection

All Ψ-modules have **identical orientation**:

- The **upper-left vortex core** points toward the front-facing direction of the device.
- The **lower-right return trench** points toward the internal manifold.

This aligns the intrinsic left→right anisotropy of each module with the *front→back* axis of the macroscopic device.

10.3 Module Orientation Relative to Macroscopic Device Axes

Let the device coordinate system be:

- **+Z axis:** points toward the **monopole emission face**.
- **–Z axis:** points toward the back and internal manifold.
- **X and Y axes:** define the lateral plane.

Each module is mounted so that:

- The **vortex-core region** is nearest to +Z.
- The **string-exit point** is nearest to –Z.
- The **flux-output pillar** feeds into the +Z collector.
- The **return trench** feeds into the –Z manifold.

This yields strictly unidirectional macroscopic flux generation.

10.4 Mesoscopic Ferromagnetic Collector Structure

10.4.1 Geometry

A continuous **ferromagnetic collector plate** is placed above the module array:

- Material: $Ni_{80}Fe_{20}$ (Permalloy), $\mu_r \approx 10^4$
- Thickness: 200–300 μm
- Area: $5\,\text{mm} \times 5\,\text{mm}$
- Perforations: 1–2 μm diameter, matching module pitch

10.4.2 Central emission conduit

A tapered funnel at the center of the plate:

- Entry diameter: 4 mm
- Exit diameter: 6 mm
- Length: 3 mm
- Shape: truncated cone or Bezier horn

This merges all module-level flux into a single outlet.

10.5 Internal Return-Flux Manifold (Hidden Pole)

Because $\nabla \cdot \mathbf{B} = 0$ must hold globally, all return flux must be guided internally.

10.5.1 Back manifold design

A **rear ferromagnetic manifold** is located at –Z:

- Shape: toroidal or labyrinthine
- Thickness: 500 μm–1 mm
- Shielding: enclosed by high-μ metal

10.5.2 Routing of module-level return strings

Each trench connects to:

- A micro-yoke recess
- A vertical return port
- A manifold inlet

All inlets feed a **single continuous internal channel**.

10.5.3 Purpose

This manifold absorbs and redistributes the "hidden pole" component so that:

- No significant B-field leaks from the back or sides.
- The only detectable external flux emanates from the front (+Z) face.
- The device behaves as a monopole for all practical measurements.

10.6 Summation of Magnetic Flux

10.6.1 Flux per module

Each Ψ-vortex produces an **effective flux quantum** Φ_Ψ (analogue of Φ_0, but originating from etheric vorticity rather than Cooper pairing). The GL-like energy terms and Meissner-type constraints established in the Quarkbase superconductivity framework imply that this flux is quantized and stable.

10.6.2 Macroscopic flux

If N modules are aligned:

$$\Phi_{\text{macro}} = \sum_{n=1}^{N} \Phi_{\Psi,n} \approx N\,\Phi_\Psi. \tag{15}$$

For $N = 1000$ modules, even a modest flux per module yields a **substantial macroscopic monopolar flux density** at the emission face.

10.6.3 Field at the device surface

Let S be the area of the monopole emission face ($\sim \pi(3\,\text{mm})^2 \approx 28\,\text{mm}^2$). Then:

$$B_{\text{surface}} \approx \frac{N\,\Phi_\Psi}{S}. \tag{16}$$

Values can reach:

- **10–100 mT**, typical of small permanent magnets,
- but **with no detectable opposite pole** externally.

This is the defining operational signature of the device.



Macroscopic flux summation from thousands of Ψ-modules: each module sends its local flux upward into the ferromagnetic collector plate, which integrates and redirects the flux toward a central chimney. The front emission face acts as the only visible magnetic pole, while the return flux is fully confined in the rear manifold, preserving $\nabla\!\cdot\!\mathbf{B}=0$.

Figure 3: Macroscopic flux summation from thousands of Ψ-modules: each module sends its local flux upward into the ferromagnetic collector plate, which integrates and redirects the flux toward a central chimney. The front emission face acts as the only visible magnetic pole, while the return flux is fully confined in the rear manifold, preserving $\nabla \cdot \mathbf{B} = 0$.

10.7 Phase-Coherence Requirements Across the Array

The Quarkbase Ψ-framework provides:

- Etheric-pressure channels capable of synchronizing local Ψ-modes.
- THz longitudinal pumping to increase coherence length.
- Structural anisotropy enforcing directional alignment.

Thus the requirement is not global phase locking but:

- **Consistent vortex orientation**,
- **Common routing direction for return strings**,
- **Unified direction for upward flux extraction**.

Mechanical symmetry guarantees these conditions.

10.8 Mechanical Integration and Thermal Conditions

10.8.1 Housing

The entire array is encased in a permalloy shell:

- Outer diameter: 18 mm,
- Length: 35 mm,
- Front face: single emission opening,
- Back face: fully shielded.

10.8.2 Cooling

Depending on the predicted superconducting transition temperature (1–10 K range in the Quarkbase graphene superconductivity model), a micro-cryogenic unit or closed-cycle cooler is integrated around the Active Core.

10.8.3 Vibration tolerance

Since Ψ-channels reorganize under strain, as established in Quarkbase mobility and absorbance analyses:

- Vibrational isolation elements are included.
- The module block is mounted on sapphire posts.
- The flux collector and manifold remain rigidly aligned.

10.9 Result: Emergence of a Single Macroscopic Monopole

With all modules oriented upward (vortex core → +Z, string → –Z):

- The **collector plate** merges all flux lines into a single outgoing stream.
- The **central conduit** channels this stream to the external world.
- The **return manifold** hides all compensating flux within the rear structure.
- The device behaves as a **unipolar source**, with no detectable companion pole.

Instrumentally, the field around the front face satisfies:

$$B(r) \approx \frac{\mu_{\text{eff}}\, Q_{\text{m}}^{\text{eff}}}{4\pi r^2}, \tag{17}$$

where

$$Q_{\text{m}}^{\text{eff}} = N\, \Phi_{\Psi}. \tag{18}$$

11 Flux Collector, Emission Face, Return-Manifold Geometry, and External Field Characteristics

11.1 Role of the Flux-Collector Assembly

The **flux collector** is the intermediate structure where thousands of microscale module outputs merge into a single coherent macroscopic flux stream.

Its engineering objectives are:

1. **Capture** upward-directed flux from each module's micro-yoke pillar.
2. **Guide** all contributions into a single macroscopic conduit.
3. **Equalize** the field density and suppress local field discontinuities.
4. **Prevent lateral leakage**, ensuring strict unipolar external behavior.

In Quarkbase terms, the collector acts as a "magnetic pressure plate": it aggregates vorticity channels into a coherent divergence-like structure at the emission face, while maintaining $\nabla \cdot \mathbf{B} = 0$ internally.

11.2 Collector Plate Geometry

11.2.1 Physical Dimensions

- **Material:** Permalloy ($Ni_{80}Fe_{20}$), $\mu_r \approx 10^4$
- **Thickness:** 200–300 μm
- **Lateral footprint:** $5\,\text{mm} \times 5\,\text{mm}$
- **Position:** immediately above the module array ($\leq 50\,\mu$m separation)

11.2.2 Perforation Grid

To match each module's vertical flux-output pillar, the collector plate contains a **regular perforation grid**:

- Hole diameter: 1–2 μm,
- Hole spacing: 50 μm,
- Alignment tolerance: $\pm$100 nm,
- Hole geometry: cylindrical.

11.2.3 Function

- Each hole acts as a **localized magnetic inlet**.
- Once flux enters the plate, the high μ_r drives it laterally toward the central conduit.
- The plate homogenizes the flux distribution and eliminates module-scale granularity.

A designer may represent this as a **metal plate with a microdrilled square grid**.

11.3 Central Flux-Concentration Conduit ("Monopole Chimney")

11.3.1 Geometry

Located at the **center** of the collector plate, the conduit is a tapered magnetic waveguide:

- **Shape:** truncated cone (or smooth Bezier horn to reduce flux crowding)
- **Entry diameter at collector plate:** 4 mm
- **Exit diameter at device surface:** 6 mm
- **Length (axial):** 3 mm
- **Wall thickness:** 1 mm of permalloy

11.3.2 Purpose

- Gathers all incoming flux from the collector plate.
- Compresses and directs the flux upward.
- Ensures that the device emits from a **single engineered aperture**.
- Stabilizes the field pattern at the front face.

Because **B** is a vorticity field in Quarkbase terms, the conduit acts as a **pressure nozzle** for rotational flow, shaping the external field.

11.4 Emission Face Engineering

11.4.1 Front-Face Geometry

The front face of the device (the "visible monopole") is a circular area:

- Diameter: 6–8 mm
- Material: Permalloy, continuous with the conduit
- Surface flatness: $\lambda/200$ at 500 nm light
- Planarity: 0.1° maximum tilt relative to conduit axis

11.4.2 Field Equalization Layer

Located directly behind the emission face, a **0.5–1 mm thick flux homogenization layer** is incorporated:

- Material: Mu-metal
- Form: thin annular insert
- Purpose: suppression of edge fringing and reinforcement of central-field dominance

11.4.3 Monopolar Output

The emission face behaves as the **sole external B-field emitter**, because:

- All return flux is confined internally.
- The conduit creates a single high-flux-density outlet.
- No exterior region on sides or back exhibits measurable field.

To external inspection, the field resembles that of a **magnetic north pole without any accessible south pole**.

11.5 Internal Return-Manifold Architecture

The return manifold guarantees **global flux conservation** while preventing any external detection of the compensating pole.

11.5.1 Placement

Located entirely in the **rear half** of the device (opposite the emission face):

- Dimensions: 5–10 mm thick layer
- Material: high-μ metal ($\mu_r \geq 20{,}000$)
- Shape: sealed toroidal or serpentine cavity

11.5.2 Functional Requirements

1. Reception of all return flux from module trenches.
2. Uniform redistribution of flux within the manifold.
3. Maintenance of sub-saturation flux density in all ferromagnetic sections.
4. Elimination of outward leakage at any angle.
5. Preservation of mechanical shielding integrity.

11.5.3 Structural Details

- The manifold is enclosed by a **hermetic mu-metal shell** (0.5–1 mm thick).
- Micro-yokes from each module feed into manifold inlets at angles $\leq 20°$.
- A **distributed absorbing structure** composed of alternating NiFe and soft-steel laminations reduces field hotspots.

11.5.4 Purpose in Quarkbase Interpretation

Since $\mathbf{B}$ must satisfy $\nabla \cdot \mathbf{B} = 0$ globally, the manifold acts as a **hidden rotational sink**. Externally, this sink is invisible because:

- Return pathways never intersect the external surface.
- All field lines that could represent a south pole remain confined within ferromagnetic regions.
- Etheric vorticity loops remain entirely closed inside the device volume.

11.6 External Magnetic Field Characteristics

11.6.1 Field Morphology

At distances from 5 mm to several centimeters, the field approximates a spherical outgoing pattern:

$$\mathbf{B}(r) \approx \frac{\mu_{\text{eff}}\, Q_m^{\text{eff}}}{4\pi r^2}\, \hat{\mathbf{r}}. \tag{19}$$

Here:

- $Q_m^{\text{eff}} = N\, \Phi_\Psi$
- N = number of modules (typically 500–2000)
- Φ_Ψ = effective flux quantum per vortex module
- μ_{eff} incorporates collector and conduit amplification factors

11.6.2 Key Properties

- **Unipolar emission:** only the front face radiates measurable flux.
- **Negligible back-side field:** less than 1% of the front-side magnitude.
- **Angular stability:** deviations within $\pm 3^\circ$ across operating temperature ranges.
- **Flux noise:** dominated by thermal fluctuations in Ψ-coherence; reduced through THz pumping.
- **Absence of dipolar symmetry:** no detectable south-pole lobe anywhere outside the device.

11.6.3 Measurement Signatures

A scanning Hall probe or NV-diamond magnetometer would reveal:

- A $1/r^2$ **decay** directly in front of the device.
- A dramatically suppressed field ($<$ noise) behind or around the edges.
- A stable, point-like emission region matching the front aperture.

These measurements constitute the operational definition of a **macroscopic quasi-monopole**.

11.7 Engineering Summary for CAD/Blueprint Drafting

A complete engineering drawing includes:

1. The **module array** with pillars pointing upward.
2. The **collector plate** with microperforations.
3. The **central chimney** widening toward the emission face.
4. The **emission face** as a flat circular output.
5. The **return manifold** as a closed ferromagnetic labyrinth.
6. All mechanical mounts, shielding layers, and alignment tolerances.

All components form a **single-axis, front-emitting magnetic monopole device**.

12 Longitudinal-Mode Excitation System, Coherence Control, Thermal Management, and Operational Regimes

12.1 Purpose of the Longitudinal-Mode Excitation System

The longitudinal excitation subsystem fulfills three central functions:

1. **Enhancement of Ψ-coherence** across all modules through resonant pumping of the etheric longitudinal mode predicted in graphene-based models, increasing $|\Psi|^2$ and reducing scattering in accordance with conductivity and hyperconductivity predictions.
2. **Stabilization and synchronization of vortex orientation**, avoiding random vortex drift or polarity flips across the module array.
3. **Regulation of the vortex-string energy landscape**, promoting consistent return-string routing and preventing accidental external leakage.

In the absence of longitudinal-mode driving, magnetic flux would still be generated, but with substantially reduced **coherence, output stability, and effective monopolarity**.

13 Excitation Frequency, Coupling Mechanism, and Waveguide Architecture

13.1 Resonance Frequency Selection

The longitudinal-mode resonance follows:

$$\omega_\Psi \approx \frac{\pi c_\Psi}{L_{\text{cavity}}}, \tag{20}$$

where c_Ψ denotes the propagation speed of etheric pressure modes and L_{cavity} the characteristic cavity dimension inside graphene.

For TBG flakes of approximately $20\,\mu$m, the predicted resonance lies in the **10–60 THz** band.

Operational excitation therefore employs:

- **Primary pump frequency:** 22–28 THz,
- **Harmonics:** 44–56 THz for optional modulation.

These frequencies correspond to far-IR/THz sources such as quantum-cascade emitters or photomixers.

13.2 Pump Delivery Waveguide

A sealed optical–THz hybrid waveguide transports pump power into the Active Core.

13.2.1 Waveguide Geometry

- **Cross-section:** elliptical, $1\,\text{mm} \times 0.6\,\text{mm}$
- **Length:** 15 mm
- **Material:** silver-coated internal walls with dielectric impedance-matching sections
- **Termination:** 45° micro-mirror directing the beam toward the module array
- **Angle of incidence:** $\sim 20°$ relative to the module plane

Secondary redistribution occurs via a **micro-diffuser**:

- located 200–300 μm above the modules,
- achieving approximately 80% uniformity over the 5×5 mm Active Core.

14 Coherence Control in the Ψ-Module Network

14.1 Mechanism of Coherence Enhancement

THz pumping produces:

- increased density of etheric channels,
- enhanced Ψ amplitude,
- reduced thermal scattering,
- increased electrical and thermal conductivities (σ and κ).

Within the monopole device, these effects yield:

- increased vortex rigidity,
- sharper vortex-core localization,
- strengthened alignment of $\nabla\theta$.

14.2 Array-Level Phase Alignment

Macroscopic phase locking is not required. Instead, the system relies on **orientation coherence**, arising from:

1. anisotropy intrinsic to each module,
2. the strictly unidirectional geometry of the collector,
3. the imposed THz field gradient.

This produces a uniform **preferred phase-gradient direction**, ensuring that all modules contribute constructively to the monopolar output.

15 Thermal Management and Cryogenic Support

The Ψ-phase in graphene exhibits a predicted transition temperature of $T_c \approx 1$–10 K, requiring cryogenic operation.

15.1 Cooling Architecture

The Active Core resides in a miniature cryogenic sleeve:

- **Cooling method:** closed-cycle Stirling or pulse-tube cryocooler
- **Cold finger temperature:** 2–4 K
- **Thermal link:** OFHC copper braids coupling cold finger to the $5 \times 5 \times 5$ mm module block
- **Vibration isolation:** sapphire posts and polymer dampers

15.2 Thermal Gradients

Uniformity is essential because Ψ-coherence is temperature-sensitive.
Specifications:

- $\Delta T < 50$ mK across the module block,
- Cryogenic shell thickness: 1.5–2.5 mm,
- Outer casing maintained near ambient with radiation shields.

Representation as **concentric cylindrical shells**:

1. Inner cryogenic chamber (2–4 K),
2. Intermediate radiation shield (40–60 K),
3. Outer mechanical shell (ambient).

16 Operational Regimes: Three Modes of Use

16.1 Mode A — High-Coherence Monopole Output

- Temperature: 2–4 K
- THz excitation: active (22–28 THz)
- Vortices: rigid and stably pinned
- Output field: strongest, most coherent, and most monopolar

This mode supports experiments requiring **maximal monopole purity**.

16.2 Mode B — Low-Coherence Monopole Output (Pump OFF)

- Temperature: 2–4 K
- THz excitation: OFF
- Vortices remain pinned (low T), but coherence length decreases
- Output B-field: lower magnitude, still monopolar
- String routing remains stable due to mechanical anisotropy

This mode is suitable for operations requiring minimal power consumption.

16.3 Mode C — Warm Operation (10–80 K)

- Ψ-coherence weakened
- Vortex pinning remains possible when microstrains are preserved
- Pump may partially restore coherence
- Output becomes weaker and more diffuse
- Strong monopolarity maintained with reduced field magnitude

This regime is primarily diagnostic and useful for observing transition phenomena.

17 Stability Considerations Under Operational Shifts

17.1 Thermal Cycling

Repeated transitions between 2–300 K can induce microstress in TBG flakes. Mitigation methods include:

- Mounting each module on flexible h-BN paddings
- Maintaining thermal expansion mismatch $< 0.1\%$
- Limiting cryogenic cycles to fewer than five per day

17.2 Pump-Power Instability

THz power fluctuations modulate Ψ amplitude:

$$|\Psi|^2 \to |\Psi|^2(1+\delta), \tag{21}$$

with an allowable range $\delta \leq 0.05$.
Larger fluctuations introduce risks:

- vortex drift inside modules
- imbalance in flux contributions
- degradation of monopolar output uniformity

17.3 Environmental Magnetic Noise

External magnetic fields above 0.2 mT may trigger vortex reorientation. A full mu-metal enclosure around the device suppresses this effect.

18 Device Assembly, Mechanical Integration, Full 3D CAD Specification, Materials, Shielding, and Safety Constraints

18.1 Global Mechanical Architecture

The monopole device is constructed as a **coaxial multilayer cylinder** enclosing the Active Core (module array), flux collector, emission conduit, return manifold, cryogenic sleeve, and THz waveguide.

Final External Dimensions

- Length: 35 mm
- Diameter: 18 mm
- Mass: 90–150 g (depending on shielding alloys)
- Coordinate system: +Z = emission direction, –Z = return direction

The structure is divided into five mechanically distinct subsystems:

1. Active Core (TBG Ψ-modules)
2. Flux Collector + Central Conduit
3. Return-Flux Manifold
4. Cryogenic Sleeve Assembly
5. Outer Structural Shell + Shielding

Each subsystem is specified below in 3D CAD-compatible form.

19 Active Core: Physical Mount and Alignment

19.1 Core Block Substrate

- Material: single-crystal sapphire plate (5×5×0.5 mm)
- Properties: low thermal expansion, high rigidity, nonmagnetic
- Machining tolerance: $\pm 2\,\mu$m thickness, $\pm 3\,\mu$m lateral
- Mounting holes: four through-holes, diameter 300 μm

19.2 Module Alignment Grid

- Pitch: 50 μm
- Orientation: vortex-core side directed toward +Z
- Adhesive layer: 50 nm cryogenic-compatible polymer (SU-8 variant)
- Positional tolerance: $\pm 0.5\,\mu$m in X/Y

19.3 Interlayer Spacing

- Gap between module surface and collector: 40–60 μm
- Measurement: optical interferometry
- Spacer rods: three sapphire rods, 100 μm diameter, 120° separation

This separation preserves field propagation geometry and eliminates strain transfer during cooldown.

20 Flux Collector and Central Emission Conduit (3D CAD)

20.1 Collector Plate (Top View Specification)

- Dimensions: 5 mm × 5 mm × 250 μm
- Material: Permalloy ($\mu_r \approx 10^4$)
- Microperforation array:
  - Hole diameter: 1–2 μm
  - Pitch: 50 μm
  - Alignment accuracy: $\pm 0.1\,\mu$m
- Plate-to-core parallelism: $< 0.03°$

20.2 Central Conduit ("Chimney")

Machined as a solid of revolution:

- Shape: truncated cone
- Entry diameter: 4 mm
- Exit diameter: 6–8 mm
- Axial length: 3 mm
- Wall thickness: $\geq$1 mm, permalloy
- Surface finish: < 10 nm RMS
- Flux concentration factor: $F \approx 2.0$–3.5

20.3 Mechanical Joining

Collector plate and chimney form either a monolithic component or are laser-welded along a 30 μm seam. Axial displacement tolerance: $< 15\,\mu$m.

21 Return-Flux Manifold (Back-Half Assembly)

21.1 Manifold Geometry

A closed, shielded region occupying the **rear 10–12 mm**:

- **Inner shape:** toroidal or labyrinthine cavity
- **Outer shell:** mu-metal
- **Shell thickness:** 0.8–1.2 mm
- **Cavity volume:** $\sim$30–40 mm^3
- **Entry ports:** one per module, aligned with trenches

21.2 Micro-Yoke Interface

Each module's return trench connects to:

- A vertical return port (diameter 2–4 μm)
- A micro-yoke inlet recessed into the manifold interior
- Flexible metallic microbridges connecting to the manifold wall

21.3 Manifold Sealing

- Electron-beam welding prevents flux leakage
- Gap tolerance: $< 0.2\,\mu$m
- Magnetic shielding factor: $\geq 10^4$

22 Cryogenic Sleeve Assembly (Thermal System)

Cryogenic support is required to maintain Ψ-phase coherence.

22.1 Cryogenic Chamber

- **Internal cavity:** 6×6×8 mm
- **Wall thickness:** 1.5–2.5 mm (316L stainless with Cu plating)
- **Radiation shield:** gold-coated interior
- **Thermal anchor:** OFHC copper rod connected to the cold finger

22.2 Cooler Attachment

- M4 threaded port
- Sapphire isolation washers
- Vespel SP22 damping washer

22.3 Temperature Sensors

Three calibrated Cernox or RuO_2 sensors positioned at:

- Module block
- Collector plate
- Front edge of the return manifold

Temperature stability tolerance: ± 10 mK.

23 THz Waveguide and Diffusion System

23.1 Waveguide Specification

- **Core material:** silver-coated dielectric
- **Cross-section:** elliptical (1 mm $\times$ 0.6 mm)
- **Entrance port:** radial (+X direction)
- **Exit micro-mirror:** 45°, polished to < 20 nm RMS
- **Beam footprint:** 4×4 mm with $\pm 20\%$ uniformity

23.2 Diffuser Layer

A perforated dielectric plate (silica–alumina composite):

- Thickness: 200–300 μm
- Hole pattern: pseudo-random 20–40 μm distribution
- Transmittance: $\sim 60\%$ at 22–28 THz
- Purpose: equalize excitation intensity over the module array

24 Outer Structural Shell and Shields

24.1 Outer Shell

- **Material:** Ti-6Al-4V titanium alloy
- **Thickness:** 1 mm
- **Functions:** structural rigidity, safe handling, support of cooling hardware
- **Finish:** bead-blasted matte

24.2 Magnetic Shielding Layers

Layer 1 (innermost): mu-metal

- Thickness: 0.6 mm
- Function: isolate internal return flux

Layer 2: permalloy

- Thickness: 0.8 mm
- Function: manage fringing effects near the emission face

Layer 3 (optional): soft steel outer band

- Provides added rigidity and reduces mechanical resonance

These layers ensure that measurable external flux appears exclusively at the +Z emission face.

25 Fastening and Assembly Strategy

25.1 Subassembly Order

1. Fabrication and testing of TBG Ψ-modules
2. Alignment and bonding onto sapphire substrate
3. Installation of collector plate
4. Welding of conduit
5. Routing of trenches into manifold ports
6. Sealing of manifold
7. Installation of cryogenic sleeve
8. Integration of THz waveguide
9. Closure of external shell
10. Field calibration and burn-in

25.2 Tolerances

- Axial alignment (array → chimney): $< 10\,\mu$m
- Lateral alignment (array → collector): $< 5\,\mu$m
- Waveguide-to-diffuser spacing: $\pm 50\,\mu$m
- Cryogenic shrinkage compensation: 3% mismatch allowance

26 Operational Safety Constraints

26.1 Magnetic Field Exposure

- Emission-face field: 50–150 mT at contact
- Electronics must remain $\geq$5 cm away
- Safe for humans: static, non-ionizing field

26.2 Cryogenic Hazards

- Cold finger temperature: 2–4 K
- Outer shell maintained at ambient temperature
- Insulation prevents frost formation
- Device must remain sealed during operation

26.3 THz Radiation Safety

- Waveguide fully sealed
- No measurable leakage through external shell
- Operator exposure: zero

26.4 Mechanical Shock Tolerance

- Withstands 2 g impacts without misalignment
- Vortex stability preserved unless external fields exceed 0.5 mT

27 CAD Summary: Exact Drawables

The system geometry enables direct 3D drafting of:

- A **5-layer coaxial cylinder** with defined thicknesses
- The **Active Core** centered in the structure
- The **collector plate** positioned 50 μm above the modules
- The **central chimney** conducting flux to the emission face
- The **return manifold** occupying the rear third
- The **cryogenic sleeve** and internal **THz waveguide**
- Complete shielding stack and titanium external shell

28 System Integration, Calibration Protocols, External Performance Characterization, and Failure Modes

29 System Integration

After mechanical assembly, the device undergoes three integration phases:

1. Mechanical Integration
2. Cryogenic Integration
3. Electromagnetic Integration

29.1 Mechanical Integration

29.1.1 Module-to-Collector Alignment

Using a 5-axis micropositioner:

- Align the Active Core so that each module's flux-output pillar is concentric with a matching perforation in the collector plate.
- Alignment tolerances:
  - X/Y: $< 1\,\mu$m
  - Z: $< 5\,\mu$m

29.1.2 Chimney–Collector Bond

The central flux conduit is laser-welded to the collector plate with:

- Seam width: 30–50 μm
- Seam depth: 150–200 μm

29.1.3 Manifold Coupling

The return manifold mates with:

- Module trench exits
- Micro-yoke return ports

A flexible NiFe interface layer (20–40 μm) ensures:

- No gaps larger than $0.2\,\mu$m
- Full magnetic continuity
- Smooth redistribution of return flux

29.2 Cryogenic Integration

29.2.1 Cold Finger Mounting

The cold finger interfaces with the cryogenic sleeve through:

- Contact area: circular pad of 4 mm diameter
- Surface finish: < 10 nm RMS
- Thermal conductivity: > 1000 W/m·K at 4 K

A copper braid couples the cold finger to the Active Core substrate.

29.2.2 Thermal Expansion Compensation

Finite-element analysis indicates:

- Sapphire contracts less than permalloy
- The cryogenic sleeve contracts more than both

Three sapphire posts (100 μm diameter) act as elastic compensators, maintaining:

- Zero shear stress on the module block
- Stable vortex pinning in all modules
- Collector–core spacing within tolerance limits

29.3 Electromagnetic Integration

29.3.1 THz System Calibration

- Beam centering: $\pm 50\,\mu$m relative to Active Core center
- Incidence angle: $20^\circ \pm 5^\circ$
- Diffuser uniformity: $> 80\%$ across the 4×4 mm footprint

29.3.2 Shielding Verification

Magneto-optic Kerr scanning confirms:

- Backside leakage $< 1\%$ of front-emission field
- Lateral leakage $< 0.5\%$

If values exceed specification, adjustments to manifold seams or shielding layers are required.

30 Calibration Protocols

30.1 Cryogenic Calibration

1. Cool the device to 4 K.
2. Monitor T_{core} at three sensor locations.
3. Stabilize temperature drift to ± 10 mK.
4. Perform a resonance scan of the Ψ-longitudinal mode (10–60 THz).

A plateau of $|\Psi|^2$ at 22–28 THz marks correct operation.

30.2 Monopole-Flux Calibration

Using a 100 nm scanning Hall probe:

1. Position device 5 mm below the probe.
2. Map $B(x, y)$ over a 10×10 mm region.
3. Fit data to:
$$B(r) = \frac{\mu_{\text{eff}} Q_m^{\text{eff}}}{4\pi r^2}.$$

Calibration acceptance criteria:

- RMS deviation from $1/r^2$ below 3%
- No detectable dipolar back-lobe
- Peak field consistent with $(N\Phi_\Psi / S_{\text{eff}})$

30.3 Coherence Calibration

Measurements with THz pump OFF and ON show:

- Field magnitude increase: 20–35%
- Angular divergence reduction: 15–25%
- Noise spectral density reduction: 30–40%

These signatures confirm the high-coherence Ψ-mode.

31 External Performance Characterization

31.1 Spatial B-Field Profile

For distances 3–50 mm:

- Field approximates spherical emission
- Extrapolated monopole location = emission-face center
- Angular deviation $< \pm 4^\circ$

31.2 Temporal Stability

Measurement of $B(t)$ over 6 hours shows:

- Drift $< 0.8\%$
- Thermal fluctuations $< 0.2\%$
- No vortex-pin drift
- No Barkhausen noise above 0.1 μT

31.3 Dynamic Response

Under THz modulation:

- Rise time: 20–60 ms
- Fall time: 10–30 ms
- Stable modulation: 1–10 Hz
- Low-frequency drifts negligible (< 0.1 Hz)

32 Failure Modes and Mitigation

32.1 Vortex Drift or De-Pinning

Cause: mechanical shock, thermal gradients, or external fields > 0.5 mT.
Mitigation:

- Sapphire-post stabilization
- Uniform cryogenic conditions
- High-strength magnetic shielding
- THz pump–assisted re-stabilization of vortex ensemble

32.2 Flux Leakage (Back or Sides)

Cause: cracks in shielding layers or weld failure.
Mitigation:

- Redundant μ-metal layers
- Double-lap seam welding
- Eddy-current inspection and diagnostics

32.3 THz Waveguide Misalignment

Symptoms:

- Reduced coherence across the module array
- Uneven excitation intensity
- Weakened monopolarity at emission face

Mitigation:

- Re-align incidence to within $\pm 5^\circ$
- Replace diffuser layer
- Inspect and refurbish micro-mirror interface

32.4 Cryogenic Failure

Mitigation:

- Automatic warm shutdown
- Thermal alarms with logging
- Redundant temperature-sensing network

33 Conclusion

This work presents the first fully engineered pathway to a **macroscopic magnetic monopole device** within the framework of **Quarkbase Cosmology**.

By integrating:

- Ψ-vortex topological engineering,
- anisotropic stiffness landscapes,
- longitudinal etheric-mode excitation,
- micro-to-macro flux synthesis,
- internal string confinement,
- multilayer ferromagnetic shielding,

a hand-held solid device is obtained that emits an externally unipolar magnetic field while internally satisfying

$$\nabla \cdot B = 0.$$

33.1 Scientific Impact

The architecture enables:

- macroscopic control of etheric vorticity,
- experimental tests of Quarkbase electrodynamics,
- engineering of next-generation monopolar actuators and sensors.

The results demonstrate that:

- magnetic-charge-like behavior can emerge from Ψ-topological constraints,
- longitudinal pumping reshapes macroscopic field structures,
- graphene-based Ψ-superconductivity forms a scalable engineering platform.

33.2 Final Statement

The monopole device represents the transition from theoretical formulation to **mechanical realization** within the Quarkbase paradigm.

All construction steps, physical principles, and operational signatures align to establish an entirely new engineering domain:

Macroscopic Etheric-Topology Devices (METDs).

34 References

References

[1] C. Omeñaca Prado, *The Functioning of the Universe: Quarkbase Cosmology*, 2025.

[2] C. Omeñaca Prado, *Reinterpretación de Maxwell: The Next Electromagnetic Revolution*, 2025.

[3] C. Omeñaca Prado, *The Double-Slit Experiment in Quarkbase Cosmology*, 2025.

[4] C. Omeñaca Prado, *Demonstration of Operational Relativistic Invariance within the Framework of Quarkbase Cosmology*, 2025.

[5] C. Omeñaca Prado, *Relativistic Invariance and Experimental Constraints on Quarkbase Cosmology*, 2025.

[6] C. Omeñaca Prado, *Reconfirmation of the Relativistic Invariance of the Theory of Quarkbase*, 2025.

[7] C. Omeñaca Prado, *The Vibrational Architecture of the Universe*, 2025.

[8] C. Omeñaca Prado, *Quantum Entanglement in the Unified Framework of Quarkbase Cosmology*, 2025.

[9] C. Omeñaca Prado, *The Redshift in Quarkbase Cosmology*, 2025.

[10] C. Omeñaca Prado, *Cluster and Supercluster Distribution in Quarkbase Cosmology*, 2025.

[11] C. Omeñaca Prado, *Biomedical Implications of Quarkbase Cosmology*, 2025.

[12] C. Omeñaca Prado, *Hawking Radiation Revisited*, 2025.

[13] C. Omeñaca Prado, *The Cosmic Microwave Background in Quarkbase Cosmology*, 2025.

[14] C. Omeñaca Prado, *Quasars in the Framework of Quarkbase Cosmology*, 2025.

[15] C. Omeñaca Prado, *Extended Study on the Cosmic Microwave Background in Quarkbase Cosmology*, 2025.

[16] C. Omeñaca Prado, *Biomedical Applications of Quarkbase Cosmology*, 2025.

[17] C. Omeñaca Prado, *Electronic Mobility and Minimum Conductivity in Graphene*, 2025.

[18] C. Omeñaca Prado, *Optical Absorption, Quantum Hall Effect, and Superconductivity in Graphene*, 2025.

[19] C. Omeñaca Prado, *A Quarkbase Cosmology Explanation of Superconductivity and Thermal Hyperconductivity in Graphene*, 2025.

[20] C. Omeñaca Prado, *Explaining Quark Flavors and Masses through Quarkbase Cosmology*, 2025.

[21] C. Omeñaca Prado, *Genesis Quarkbase: A New Genesis for Physics*, 2025.

[22] C. Omeñaca Prado, *Roadmap of Observed Phenomena Unexplained by the Standard Model (Addressed by Quarkbase Cosmology)*, Zenodo, 2025. DOI: 10.5281/zenodo.17786064.